

1




L-Steckverschraubungen, langer Körper, zylindrisches Gewinde

Standard

Typ	G	D
IQSLLK M54	M 5	4
IQSLLK M56	M 5	6
IQSLLK 184 G	G 1/8"	4
IQSLLK 186 G	G 1/8"	6
IQSLLK 188 G	G 1/8"	8
IQSLLK 1810 G	G 1/8"	10

Typ	G	D
IQSLLK 144 G	G 1/4"	4
IQSLLK 146 G	G 1/4"	6
IQSLLK 148 G	G 1/4"	8
IQSLLK 1410 G	G 1/4"	10
IQSLLK 1412 G	G 1/4"	12
IQSLLK 386 G	G 3/8"	6

Typ	G	D
IQSLLK 388 G	G 3/8"	8
IQSLLK 3810 G	G 3/8"	10
IQSLLK 3812 G	G 3/8"	12
IQSLLK 1210 G	G 1/2"	10
IQSLLK 1212 G	G 1/2"	12



Steckverschraubungen 45°

Standard

Typ	R	D
IQSW 184	R 1/8"	4
IQSW 186	R 1/8"	6
IQSW 188	R 1/8"	8
IQSW 1810	R 1/8"	10
IQSW 144	R 1/4"	4
IQSW 146	R 1/4"	6

Typ	R	D
IQSW 148	R 1/4"	8
IQSW 1410	R 1/4"	10
IQSW 1412	R 1/4"	12
IQSW 386	R 3/8"	6
IQSW 388	R 3/8"	8
IQSW 3810	R 3/8"	10

Typ	R	D
IQSW 3812	R 3/8"	12
IQSW 128	R 1/2"	8
IQSW 1210	R 1/2"	10
IQSW 1212	R 1/2"	12



Steckverschraubungen 45°, zylindrisches Gewinde

Standard

Typ	G	D
IQSW M54	M 5	4
IQSW M56	M 5	6
IQSW 184 G	G 1/8"	4
IQSW 186 G	G 1/8"	6
IQSW 188 G	G 1/8"	8
IQSW 1810 G	G 1/8"	10

Typ	G	D
IQSW 144 G	G 1/4"	4
IQSW 146 G	G 1/4"	6
IQSW 148 G	G 1/4"	8
IQSW 1410 G	G 1/4"	10
IQSW 1412 G	G 1/4"	12
IQSW 386 G	G 3/8"	6

Typ	G	D
IQSW 388 G	G 3/8"	8
IQSW 3810 G	G 3/8"	10
IQSW 3812 G	G 3/8"	12
IQSW 128 G	G 1/2"	8
IQSW 1210 G	G 1/2"	10
IQSW 1212 G	G 1/2"	12



L-Steckverschraubungen mit Innengewinde

Standard

Typ	G	D
IQSLF M54	M 5	4
IQSLF M56	M 5	6
IQSLF 184	G 1/8"	4
IQSLF 186	G 1/8"	6
IQSLF 188	G 1/8"	8

Typ	G	D
IQSLF 144	G 1/4"	4
IQSLF 146	G 1/4"	6
IQSLF 148	G 1/4"	8
IQSLF 1410	G 1/4"	10
IQSLF 1412	G 1/4"	12

Typ	G	D
IQSLF 386	G 3/8"	6
IQSLF 388	G 3/8"	8
IQSLF 3810	G 3/8"	10
IQSLF 1210	G 1/2"	10
IQSLF 1212	G 1/2"	12



L-Steckverschraubungen mit Außensechskant

Standard

Typ	R	D
IQSLV 184	R 1/8"	4
IQSLV 186	R 1/8"	6
IQSLV 188	R 1/8"	8
IQSLV 146	R 1/4"	6

Typ	R	D
IQSLV 148	R 1/4"	8
IQSLV 1410	R 1/4"	10
IQSLV 1412	R 1/4"	12
IQSLV 388	R 3/8"	8

Typ	R	D
IQSLV 3810	R 3/8"	10
IQSLV 3812	R 3/8"	12
IQSLV 1210	R 1/2"	10
IQSLV 1212	R 1/2"	12



L-Steckverschraubungen mit Außensechskant, zylindrisches Gewinde

Standard

Typ	G	D
IQSLV M53*	M 5	3
IQSLV M54*	M 5	4
IQSLV M56*	M 5	6
IQSLV 184 G	G 1/8"	4
IQSLV 186 G	G 1/8"	6

Typ	G	D
IQSLV 188 G	G 1/8"	8
IQSLV 146 G	G 1/4"	6
IQSLV 148 G	G 1/4"	8
IQSLV 1410 G	G 1/4"	10
IQSLV 388 G	G 3/8"	8

Typ	G	D
IQSLV 3810 G	G 3/8"	10
IQSLV 3812 G	G 3/8"	12
IQSLV 1210 G	G 1/2"	10
IQSLV 1212 G	G 1/2"	12

* nur während der Montage positionierbar



L-Steckverschraubungen mit Innensechskant

Standard

Typ	R	D
IQSLV 184 I	R 1/8"	4
IQSLV 186 I	R 1/8"	6
IQSLV 188 I	R 1/8"	8
IQSLV 146 I	R 1/4"	6

Typ	R	D
IQSLV 148 I	R 1/4"	8
IQSLV 1410 I	R 1/4"	10
IQSLV 388 I	R 3/8"	8
IQSLV 3810 I	R 3/8"	10

Typ	R	D
IQSLV 3812 I	R 3/8"	12
IQSLV 1210 I	R 1/2"	10
IQSLV 1212 I	R 1/2"	12