
semi-rotary drive DRRD-25-180-FH-PA Part number: 1359980 ★ Core product range







Data sheet

| Feature | Value |
|---|--|
| Size | 25 |
| Cushioning angle | 33 deg |
| Setting range of swivel angle on both sides | +10 /-100 deg |
| Swivel angle | 180 deg |
| Cushioning | P: Flexible cushioning rings/plates at both ends |
| Assembly position | Any |
| Design structure | Rack and pinion |
| Position detection | For proximity sensor |
| Operating pressure | 3 8 bar |
| Mode of operation | double-acting |
| Operating medium | Compressed air in accordance with ISO8573-1:2010 [7:4:4] |
| Note on operating and pilot medium | Lubricated operation possible (subsequently required for further |
| | operation) |
| Ambient temperature | -10 60 °C |
| Theoretical torque at 6 bar | 5.15 Nm |
| Permissible mass moment of inertia | 0.09 kgm2 |
| Product weight | 1,349 g |
| Mounting type | Optional |
| | with through hole |
| | with internal (female) thread |
| Pneumatic connection | M5 |
| Materials note | Contains PWIS substances |
| | Conforms to RoHS |
| Material of drive shaft | Heat-treatment steel |
| Material cover | Wrought Aluminium alloy |
| | Anodised |
| Material seals | NBR |
| | TPE-U(PU) |
| Material housing | Wrought Aluminium alloy |
| | Smooth anodised |