


lubricator MS9-LOE-G-U

Part number: 564144

FESTO

Metal bowl, direction of flow: from left to right.



Data sheet

| Feature | Value |
|---|--|
| Size | 9 |
| Series | MS |
| Assembly position | Vertical +/- 5° |
| Design structure | proportional standard mist lubricator |
| Max. oil capacity | 490 ml |
| Bowl guard | integrated as metal shell |
| Operating pressure | 1 ... 16 bar |
| Minimum flow rate for lubricator function | 100 l/min |
| Operating medium | Air quality class 5:7:- per DIN ISO 8573-1 |
| Corrosion resistance classification CRC | 2 - Moderate corrosion stress |
| Storage temperature | -10 ... 60 °C |
| Medium temperature | -10 ... 60 °C |
| Oil viscosity | ISO VG 32 |
| Ambient temperature | -10 ... 60 °C |
| Product weight | 2,000 g |
| Mounting type | Line installation with accessories |
| Material of cover | PA-reinforced |
| Materials note | Conforms to RoHS |
| Material of connecting plate | Aluminium die cast |
| Material seals | NBR |
| Material housing | Aluminium die cast |
| Material module connector | Aluminium die cast |
| Material bowl | Wrought Aluminium alloy |
| Material cup seal | NBR |
| Material screen | PA |