



HOSES

Material PVC



Part No.	D1	D	L (m)	Colour	Working Pressure (Bar)	Burst Pressure (Bar)	Bend Radius	
P10T	10	16	30	Grey	17	51	65	1
P10B	10	16	30	Blue	17	51	65	1
P10R	10	16	30	Red	17	51	65	1
P13T	13	19	30	Grey	15	45	85	1
P13B	13	19	30	Blue	15	45	85	1
P13R	13	19	30	Red	15	45	85	1
P19T	19	26	30	Grey	10	30	125	1
P19B	19	26	30	Blue	10	30	125	1
P19R	19	26	30	Red	10	30	125	1

Tube:
Transparent soft PVC hose for low temperature water and air.

Cover:
Clear, blue or red transparent soft PVC. Resistant to abrasion, ozone, and weather.

Temperature range:
Working temperature: Up to +60°C (+140°F) peak up to +90°C (+194°F).
Note: Lifetime of this hose will be substantially reduced if operating temperatures exceed +60°C (+140°F).



Tolerances:
UNI EN ISO 1307/97 tolerances for inside diameters up to and including 25 mm.

Reinforcement:
High-strength PES fiber.

Applications:
Flexible hose designed for cold water for mould temperature controlling.

On inside diameter:
for I.D. 5.1 up to 20 mm ± 0.80 mm.
Length tolerance: ± 1%.

Material Silicone - Steam Resistant



Part No.	D1	D	L (m)	Colour	Working Pressure (Bar)	Burst Pressure (Bar)	Bend Radius	
S10	10	15	25	Grey	15	45	40	1
S10B	10	15	25	Blue	15	45	40	1
S10R	10	15	25	Red	15	45	40	1
S13	13	19	25	Grey	15	45	60	1
S13B	13	19	25	Blue	15	45	60	1
S13R	13	19	25	Red	15	45	60	1
S19	19	29	25	Grey	15	45	100	1
S19B	19	29	25	Blue	15	45	100	1
S19R	19	29	25	Red	15	45	100	1

Tube:
Clear Silicone Shore 60°.

Applications:
Designed for water and light chemical media for mould temperature controlling.

Temperature range:
Working temperature: Max +170°C / +338°F.

Tolerances:
DIN 7715.

Reinforcement:
Stainless steel overbraid with colour marking made of textile meta aramid. (high temperature resistant)

See explanation of symbols on page 404