



HOSES

Material EPDM



Part No.	D1	D	L (m)	Colour	Working Pressure (Bar)	Burst Pressure (Bar)	Bend Radius	
E10B	10	16,5	50	Blue	15	60	60	1
E10R	10	16,5	50	Red	15	60	60	1
E10S	10	16,5	50	Black	15	60	60	1
E13B	13	21	50	Blue	15	60	90	1
E13R	13	21	50	Red	15	60	90	1
E13S	13	21	50	Black	15	60	90	1
E19B	19	27	30	Blue	15	60	110	1
E19R	19	27	30	Red	15	60	110	1
E19S	19	27	30	Black	15	60	110	1

Tube:

Black, antistatic, smooth EPM Nitrosamine free rubber compound, resistant to heat, hot water and water Vapour.

Reinforcement:

Synthetic textile yarns.

Cover:

Blue, Red, or Black smooth EPDM Nitrosamine free rubber compound. Resistant to abrasion, ozone, heat, and weather.

Applications:

Flexible hose designed for hot water and water vapour for mould temperature controlling.

Temperature range:

Working temperature: Up to +140°C (+284°F) peak up to +164°C (+327°F).
Note: Lifetime of this hose will be substantially reduced if operating temperatures exceed +130°C (+266°F).



Tolerances:

UNI EN ISO 1307/97 tolerances for inside diameters up to and including 25 mm.

On inside diameter:

for I.D. 5.1 up to 20 mm ± 0.80 mm.
Length tolerance: ± 1%.

Material EPDM



Part No.	D1	D	L (m)	Colour	Working Pressure (Bar)	Burst Pressure (Bar)	Bend Radius	
G10B	10	16,5	50	Blue	15	60	60	1
G10R	10	16,5	50	Red	15	60	60	1
G10S	10	16,5	50	Black	15	60	60	1
G13B	13	21	50	Blue	15	60	90	1
G13R	13	21	50	Red	15	60	90	1
G13S	13	21	50	Black	15	60	90	1
G19B	19	27	30	Blue	15	60	110	1
G19R	19	27	30	Red	15	60	110	1
G19S	19	27	30	Black	15	60	110	1
G25B	25	35	20	Blue	15	60	130	1
G25R	25	35	20	Red	15	60	130	1
G38B	38	48	20	Blue	10	30	200	1
G38R	38	48	20	Red	10	30	200	1

Tube:

Black, antistatic, smooth EPDM Nitrosamine free rubber compound, resistant to water, hot water, air, light-chemical media.

Reinforcement:

Synthetic textile yarns.

Cover:

Red, Blue or Black smooth EPDM Nitrosamine free rubber compound.

Applications:

Designed for air, cold and hot water, and light-chemical media for mould temperature controlling.

Temperature range:

Working temperature: Up to +100°C (+248°F).

Tolerances:

UNI EN ISO 1307/97 tolerances for inside diameters up to and including 25 mm.

On inside diameter:

for I.D. 5.1 up to 20 mm ± 0.80 mm.
Length tolerance: ± 1%.

See explanation of symbols on page 404