

WODEX CONICAL STEP DRILLS

ITEM: WX7550

Conical step drills **PREMIUM QUALITY** in HSS steel with high surface resistance, suitable for drilling ferrous materials, aluminum, copper and plastic materials with thicknesses up to 5 mm. Dimensions of the drilling diameters laser engraved on the groove and cylindrical shank with driving planes.

Specifications:

N522713A - WX7550/13A	Ø 4-5-6-7-8-9-10-11-12-13 mm
N522722A - WX7550/22A	Ø 4-7-10-13-16-19-22 mm
N522723A - WX7550/23A	Ø 5-8-11-14-17-20-23 mm
N522724A - WX7550/24A	Ø 6-9-12-15-18-21-24 mm
N522724B - WX7550/24B	Ø 6-8-10-12-14-16-18-20-22-24 mm
N522730A - WX7550/30A	Ø 4-6-8-10-12-14-16-18-20-22-24-26-28-30 mm
N522732A - WX7550/32A	Ø 6,5-9,8-11-12,5-14-15,3-17,2-18,7 20,5-22,5-24,7-26,7-28,5-30,5-32,5 mm
N522740A - WX7550/40A	Ø 7-10,5-12,5-14,5-16,5-18,5-20,5 23,5-25,5-30,5-34-38,5-40,5 mm
N522742A - WX7550/42A	Ø 6-10-14-18-22-26-30-34-38-42 mm
N522743A - WX7550/43A	Ø 7-11-15-19-23-27-31-35-39-43 mm
N522744A - WX7550/44A	Ø 8-12-16-20-24-28-32-36-40-44 mm
N522745A - WX7550/45A	Ø 9-13-17-21-25-29-33-37-41-45 mm
N522750A - WX7550/50A	Ø 9-13-17-21-25-29-33-37-41-45-50 mm
N5227PG - WX7550/PG	Ø 6- 9-12,5-15-18,6-20,5-22,5-26-28,5-30,5-34-37,5 mm

Tech. Code		Ø min/max mm	Progression mm	Ø shank mm	Length mm	
N522713A		4 - 13	1	8	80	1
N522722A		4 - 22	3		64	
N522723A		5 - 23				
N522724A		6 - 24		9		
N522724B			88			
N522730A		4 - 30	2		100	
N522742A		6 - 42	4	82		
N522743A		7 - 43		11	84	
N522744A		8 - 44				
N522745A		9 - 45				
N522750A		9 - 50		4 - 5	89	
N522732A		6,5 - 32,5	-	10	120	
N522740A		7 - 40,5			115	
N5227PG		6 - 37,5	PG (*)		100	

(*) Execution of through holes for cable gland fittings with PG thread

ITEM: WX7555

Conical step drills **PREMIUM QUALITY** in HSS-CO steel with high surface resistance, suitable for drilling ferrous materials, aluminum, copper and plastic materials with thicknesses up to 5 and 10 mm. Dimensions of the drilling diameters laser engraved on the groove and cylindrical shank with driving planes.

Specifications:

Drilling up to 10 mm

N522823A - WX7555/23A	Ø 5-8-11-14-17-20-23 mm
N522824A - WX7555/24A	Ø 6-9-12-15-18-21-24 mm
N522825A - WX7555/25A	Ø 7-10-13-16-19-22-25 mm

Drilling up to 5 mm

N522836A - WX7555/36A	Ø 6-9-12-15-18-21-24-27-30-33-36 mm
N522837A - WX7555/37A	Ø 7-10-13-16-19-22-25-28-31-34-37 mm
N522838A - WX7555/38A	Ø 8-11-14-17-20-23-26-29-32-35-38 mm

Tech. Code		Ø min/max mm	Progression mm	Ø shank mm	Length mm	
N522823A		5 - 23	3	10	110	1
N522824A		6 - 24				
N522825A		7 - 25				
N522836A		6 - 36		11	97	
N522837A		7 - 37				
N522838A		8 - 38				