

ALGRA DRIVEN TOOL HOLDERS BMT55

ITEM: C5535

For lathes: **DOOSAN**: Lynx300 (M), Puma 230/240/280 (M,LM,S), Puma 1500/2000/2500 (M,S,Y), Puma 2100 (Y,LY,SY,LSY), Puma GT2100/2600 (M), Puma H250TM, Puma MX1600/2100 (ST/LST), Puma TL2000/2500 (M,LM), Puma TT1500/1800 (MS,SY), Puma TW2600M; **GOODWAY**: GTX-2000, 2600, GTZ-2000, 2600; **HYUNDAI WIA**: HD2200 M/MC, L160, 230MA/LMA/LMSA, LM1600, 1800TTSY, SKT160, 180TTMS/TTSY; **HARDINGE**: T-51/65 Super-Precision; **HWACHEON**: Cutex-160, 180 MC/ SMC/YMC/YSCM, VT 450 MC; **SAMSUNG**: SL 1500, 2000 M/SY, PL 240LM; **JYOTI**: AX300; **VICTOR**: Vturn-A16/20 CM, SCM, YCM, YSCM; Vturn-Q200.

1

2

3

Tech. Code	MODEL	Description	Figure
C5535RAPPS25	RAPPS 25 121UT55	Driven tool holder axial 0°, collet ER25, external coolant, 8000 rpm; i=1:1	1
C5535ROPSS20	ROPSS 20 121UT55	Driven tool holder orientable ± 90°, collet ER20, external coolant, 8000 rpm; i=1:1	3
C5535RRPPS2570	RRPPS 25 321UT55	Driven tool holder radial 90°, collet ER25, H=70,external coolant, 8000 rpm; i=1:1	2
C5535RRPPS2585	RRPPS 25 421UT55	Driven tool holder radial 90°, collet ER25, H=85, external coolant, 8000 rpm; i=1:1	

ALGRA STATIC TOOL HOLDERS BMT55

ITEM: C5537

For lathes: **DOOSAN**: Lynx300 (M), Puma 230/240/280 (M,LM,S), Puma 1500/2000/2500 (M,S,Y), Puma 2100 (Y,LY,SY,LSY), Puma GT2100/2600 (M), Puma H250TM, Puma MX1600/2100 (ST/LST), Puma TL2000/2500 (M,LM), Puma TT1500/1800 (MS,SY), Puma TW2600M; **GOODWAY**: GTX-2000, 2600, GTZ-2000, 2600; **HYUNDAI WIA**: HD2200 M/MC, L160, 230MA/LMA/LMSA, LM1600, 1800TTSY, SKT160, 180TTMS/TTSY; **HARDINGE**: T-51/65 Super-Precision; **HWACHEON**: Cutex-160, 180 MC/ SMC/YMC/YSCM, VT 450 MC; **SAMSUNG**: SL 1500, 2000 M/SY, PL 240LM; **JYOTI**: AX300; **VICTOR**: Vturn-A16/20 CM, SCM, YCM, YSCM; Vturn-Q200.

1

2

3

Tech. Code	MODEL	Description	Figure
C5537E10U25	E10/U 25 T55X65	Static tool holder axial Q=25,external coolant	1
C5537E10B4060	E10/B 40 T55X60	Static tool holder for boring bars, D=40, H=60, Internal/external coolant	2
C5537E10B4070	E10/B 40 T55X70	Static tool holder for boring bars, D=40, H=70, Internal/external coolant	
C5537E10BD25	E10/BD 25 T55X/110	Static tool holder for boring bars, D=25, H=65/110, Internal/external coolant	3