

SAFETY COUPLINGS & NIPPLES - SERIES 320 ESAFE, DN 7.6

ITEM: 10-320-520

Nipples - Female thread.

Tech. Code	L516214	L516238	L516212
Female thread	1/4" BSP	3/8" BSP	1/2" BSP
Air flow	2250 l/min (79.4 CFM)		
Maximum pressure	16 bar (232 PSI)		
Standard	Original CEJN Series 320 DN7.6 - Eurostandard 7.4 mm		

ITEM: 10-320-506

Nipples - Stream Line hose connection.

Tech. Code	L516406	L516408	L516411
For tubes Ø	6.5 x 10	8 x 12	11 x 16
Air flow	2250 l/min (79.4 CFM)		
Maximum pressure	16 bar (232 PSI)		
Standard	Original CEJN Series 320 DN7.6 - Eurostandard 7.4 mm		

COMPACT MULTIPLE VENTED SAFETY OUTLETS - SERIES 320 ESAFE MULTI-LINK

ITEM: 10-902-920

With multiple outlets Series 320 eSafe Multi-Link offers both flexibility and high performance. eSafe complies with ISO Standard 4414 and EN 983 and it offers standard features; one-hand operated, high flow and long service life.

Tech. Code	L517002	L517003
Connection	2	3
Female thread	1/2" BSP	
Air flow	2250 l/min (79.4 CFM)	
Maximum pressure	16 bar (232 PSI)	
Standard	Original CEJN Series 320 DN7.6 - Eurostandard 7.4 mm	

QUICK COUPLINGS FEMALE WITH MALE THREAD - MIGNON DN5

ITEM: 111

Mignon DN Series 5 mm sockets with a nickel-plated brass body and NBR seals.

Operating pressure 0-12 BAR.

Version with cylindrical male Gas thread compliant with ISO 228 Class A.

Compatible with:

- RECTUS/PARKER 21/90 profile
- CAMOZZI 5050 - 5150 profile
- CEJN 200 profile

Tech. Code	L548018	L548014
Thread	BSP 1/8"	1/4"
	10	

QUICK COUPLINGS FEMALE WITH FEMALE THREAD - MIGNON DN5

ITEM: 112

Mignon DN Series 5 mm sockets with a nickel-plated brass body and NBR seals.

Operating pressure 0-12 BAR.

Version with cylindrical female Gas thread compliant with ISO 228 Class A.

Compatible with:

- RECTUS/PARKER 21/90 profile
- CAMOZZI 5050 - 5150 profile
- CEJN 200 profile

Tech. Code	L548218	L548214
Thread	BSP 1/8"	1/4"
	10	