

ITEM: M7510

Swivel eye bolts in grade 80 steel with ring adjustable under load. Suitable for lifting and tilting loads fitted with a threaded hole. Safety factor 4 in all load directions. Rotates through 360° with ring that pivots 180°, self-aligning. Tested for 20,000 stress cycles.

Tech. Code	Size	Capacity kg	A mm	B mm	C mm	E mm	H mm	SW mm	D1 mm	Weight kg
M7510M0816	M8 x 16	300	30	13	46	50	105	30	38	0.48
M7510M1018	M10 x 18									
M7510M1218	M12 x 18	500								0.50
M7510M1620	M16 x 20	1125								0.53
M7510M2030	M20 x 30	2000	34	16	57	61	131	40	50	1.05
M7510M2430	M24 x 30	3150	40	18	70	68	153	48	58	1.63
M7510M3035	M30 x 35	5300	45	22	65	80	165	65	75	2.23

Also available in grade 60 stainless steel.

ITEM: M7515

Bolt-on swivel eye bolts for 90° load, in grade 80 steel, takes up minimal space. Anchor point for lifting loads fitted with a threaded hole. Safety factor 4 in all load directions. Can rotate through 360° when not loaded. Suitable for anchor points up to 90°. Tested for 20,000 stress cycles.

Tech. Code	Size	Capacity kg	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	I mm	L mm	W mm	J mm	K mm	CH mm	Weight kg
M7515M08	M8	300	57	34	10	78	24	41	30	26.5	25	15	43	51	35	13	0.275
M7515M10	M10	630											42			17	0.29
M7515M12	M12	1000	66	38	13.5	85	30	50	36	33	32	23	40	52	28	19	0.50
M7515M16	M16	1500										24	38			24	0.51
M7515M20	M20	2500	87	55	16	111	48	68	44	42.5	45	31	54	71	36	30	1.25
M7515M24	M24	4000										37	51			36	1.30
M7515M27	M27			109	66	22.5	145	54	91	63	58.5	60	64	86	47	41	3.15
M7515M30	M30	5000	45										62			46	3.25

Also available in grade 60 stainless steel.

ITEM: M7520

Swivel eye bolts in grade 80 steel. Anchor point for lifting loads fitted with a threaded hole. Safety factor 4 in all load directions. Can rotate through 360° when not loaded. Suitable for anchor points up to 90°. Tested for 20,000 stress cycles.

Tech. Code	Size	Capacity kg	A mm	B mm	C mm	D mm	E mm	F mm	K mm	L mm	CH mm	Weight kg
M7520M08	M8	300	33.7	10	9.8	25	25.5	30	46	12	6	0.12
M7520M10	M10	400								15		
M7520M12	M12	750	41.5	12.5	11.5	30	30.6	36.5	55.5	18	8	0.20
M7520M16	M16	1500	49.5	14.5	15.7	35	36.5	42	64.5	24	10	0.35
M7520M20	M20	2300	58	16	18	40	42	52.5	74.5	30	12	0.60
M7520M24	M24	3200	69	20.5	22	49	50	61	90	36		1
M7520M27	M27											
M7520M30	M30	4500	86	25.5	28	60	66	75	111	45	17	2

Also available in grade 60 stainless steel.