




## WODEX SCREWDRIVERS INSULATED SERIES FOR SLOTTED SCREWS

### ITEM: WX4030

Screwdrivers **PREMIUM QUALITY** for slotted screws with Isolated blade and handle up to 1000 V Din EN 60900 / VDE 0682-201. Blade in chrome vanadium steel and precision tips **BLACK-TIP** hardened with surface hardness  $58 \pm 2$  HRC and torque 20% higher than the normal DIN standard 8764. **ERGOFORM** hypoallergenic grip handle, anti-slip, soft and comfortable, made in **SANTOPRENE**® which guarantees maximum resistance for quick and accurate work. Identification of the measurement on the head of the handle. Compliant with the directives RoHS and REACH.






Tech. Code	 mm	a mm	L mm	Tech. Code	 mm	a mm	L mm
E56452,5X075	2,5x0,4	75	160	E56454,0X100	4,0x0,8	100	200
E56453,0X100	3,0x0,5	100	185	E56455,5X125	5,5x1,0	125	225

## SCREWDRIVERS INSULATED SERIES FOR SLOTTED SCREWS 160I VDE

### ITEM: 160 I VDE 1000 VOLT

Screwdrivers VDE Isolated up to 1000 volts, compliant with standard regulations IEC 60900 for slotted screws, Isolated round blade with Lasertip surface treatment of the tip. **Kraftform Plus** grip handle multi-component anti-rolling (measurement 2,5x80 and 3,0x100 without Lasertip treatment).



Tech. Code	 mm	Ø blade mm	a mm	L mm	Tech. Code	 mm	Ø blade mm	a mm	L mm
E56502,5X080	2,5x0,4	2,5	80	61	E56505,5X125	5,5x1,0	5,5	125	223
E56503,0X100	3,0x0,5	3	100	181	E56506,5X150	6,5x1,2	6,5	150	255
E56503,5X100	3,5x0,6	3,5			E56508,0X175	8,0x1,2	7	175	287
E56504,0X100	4,0x0,8	4			E565010X200	10,0x1,6	9	200	312

The Ø blade refers to terminal part without isolation.

## WODEX SINGLE-POLE VOLTAGE TESTERS STANDARD VDE

### ITEM: WX4190

Single-pole voltage testers unipolar **PREMIUM QUALITY** standard VDE 0680/6.

- Field of control 105-250 Volts
- Chrome vanadium satined steel blade




Tech. Code	 mm	Ø blade mm	a mm	L mm
E589703	3,0 x 0,5	3	70	145

## SINGLE-POLE VOLTAGE TESTERS STANDARD VDE

### ITEM: 247

Single-pole voltage testers for unipolar cables to direct the voltage in a range from 150 to 250 Volts, compliant to standard regulations ISO 57680/6 and VDE 0680/6. Ergonomic grip handle clip.




Tech. Code	 mm	Ø blade mm	a mm	L mm
E589803	3,0x0,5	3	70	151

## SINGLE-POLE VOLTAGE TESTERS

### ITEM: E5900

Single-pole voltage testers to detect the voltage in a range from 220 to 250 volts, handle grip with clip.



Tech. Code	 mm	Ø blade mm	a mm	L mm
E590003	3,0x0,5	3	65	140