The MOULDPRO Removable Nozzle Tip System saves Time and Money!

The Quick Change nozzle tip system was developed to offer a fast an economical solution for injection moulders to adapt their moulding machines to different tools and materials.

By replacing the manufacturers nozzle body with the MOULDPRPO replaceable tip design the moulder can benefit from using MOULDPRO standard 'quick change' replaceable tips.

The tips are available in different lengths, with different tip radius and orifice; the tips are available as General Purpose / Nylon Reverse Taper or ABS Full Taper.

- High Quality
- · Hardened Tool Steel
- · All Standard Sizes in Stock
- · Standardise your factory and Save Money
- · Standardise Size of Nozzle Heater Bands
- · Custom designs available



Removable Nozzle Tips

| eneral Purpose Type | Nylon Type | Full Taper | | | | |
|---------------------|----------------|---------------|-------------|--------------|--------|-----------|
| - Commission | - Comming | Samme. | | | | |
| Part Number | Part Number | Part Number | Thread Type | Total Length | Radius | Orifice Ø |
| GP1-R12.7-1.5 | | | 7/8" UNF | 38 | 12,7 | 1,5 |
| GP1-R12.7-2 | | | | | | 2 |
| GP1-R12.7-2.5 | | | | | | 2,5 |
| GP1-R12.7-3 | NRT1-R12.7-3 | FT1-R12.7-3 | | | | 3 |
| GP1-R12.7-4 | NRT1-R12.7-4 | FT1-R12.7-4 | | | | 4 |
| GP1-R12.7-5 | NRT1-R12.7-5 | FT1-R12.7-5 | | | | 5 |
| GP1-R12.7-6.5 | NRT1-R12.7-6.5 | FT1-R12.7-6.5 | | | | 6,5 |
| GP1-R12.7-8 | NRT1-R12.7-8 | FT1-R12.7-8 | | | | 8 |
| GP1-R15-1.5 | | | | | 15 | 1,5 |
| GP1-R15-2.5 | | | | | | 2,5 |
| GP1-R15-3 | NRT1-R15-3 | FT1-R15-3 | | | | 3 |
| GP1-R15-4 | NRT1-R15-4 | FT1-R15-4 | | | | 4 |
| GP1-R15-5 | NRT1-R15-5 | FT1-R15-5 | | | | 5 |
| GP1-R15-5.5 | NRT1-R15-5.5 | FT1-R15-5.5 | | | | 5,5 |
| GP1-R15-6.5 | NRT1-R15-6.5 | FT1-R15-6.5 | | | | 6,5 |
| GP1-R15-7 | NRT1-R15-7 | FT1-R15-7 | | | | 7 |
| GP1-R15-8 | NRT1-R15-8 | FT1-R15-8 | | | | 8 |
| GP1-R15-9.5 | NRT1-R15-9.5 | FT1-R15-9.5 | | | | 9,5 |
| GP1-R19-3 | NRT1-R19-3 | FT1-R19-3 | | | 19 | 3 |
| GP1-R19-4 | NRT1-R19-4 | FT1-R19-4 | | | | 4 |
| GP1-R19-5.5 | NRT1-R19-5.5 | FT1-R19-5.5 | | | 30 | 5,5 |
| GP1-R30-3 | NRT1-R30-3 | FT1-R30-3 | | | | 3 |
| GP1-R30-7 | NRT1-R30-7 | FT1-R30-7 | | | | 7 |
| GP2-R12.7-3 | NRT2-R12.7-3 | | | 70 | 12,7 | 3 |
| GP2-R19-3 | NRT2-R19-3 | | | | 19 | 3 |
| GP3-R12.7-3 | NRT3-R12.7-3 | | | 95 | 12,7 | 3 |
| GP4-R12.7-3 | NRT4-R12.7-3 | | | 127 | 12,7 | 3 |

Removeable Nozzle tips, Heat Treated Tool Steel, Polished Radius and Bore.