

Abrasive Fleece, Shank Ø 3 mm, Triple-Layer

NEW



	Part No.	Head dimensions	Grit Size	Shank dimensions	Rotation speed max.	
Ideally suited for all metals. High stock removal on aluminium, gold and silver. • very coarse grade	M-15082	Ø 22 x 13 mm	K 60	Ø 3 x 40 mm	10000 1/min	10 pieces
	M-15062	Ø 30 x 17 mm	K 60	Ø 3 x 40 mm	8000 1/min	10 pieces
	M-15072	Ø 40 x 22 mm	K 60	Ø 3 x 40 mm	8000 1/min	10 pieces
For processing all materials, ideal for removing small scratches, for deburring etc.	M-15084	Ø 22 x 13 mm	K 80	Ø 3 x 40 mm	10000 1/min	10 pieces
	M-15064	Ø 30 x 17 mm	K 80	Ø 3 x 40 mm	8000 1/min	10 pieces
	M-15074	Ø 40 x 22 mm	K 80	Ø 3 x 40 mm	8000 1/min	10 pieces
Very well suited for processing aluminium and stainless steel. • very firm grade.	M-15086	Ø 22 x 13 mm	K 180	Ø 3 x 40 mm	10000 1/min	10 pieces
	M-15066	Ø 30 x 17 mm	K 180	Ø 3 x 40 mm	8000 1/min	10 pieces
	M-15076	Ø 40 x 22 mm	K 180	Ø 3 x 40 mm	8000 1/min	10 pieces
For processing all metals, highly versatile	M-15088	Ø 22 x 13 mm	K 240	Ø 3 x 40 mm	10000 1/min	10 pieces
	M-15068	Ø 30 x 17 mm	K 240	Ø 3 x 40 mm	8000 1/min	10 pieces
	M-15078	Ø 40 x 22 mm	K 240	Ø 3 x 40 mm	8000 1/min	10 pieces
Using this grinding fleece results in a slight shine. Ideal for aluminium, stainless steels, etc.	M-25100	Ø 22 x 13 mm	K 400	Ø 3 x 40 mm	10000 1/min	10 pieces
	M-25105	Ø 25 x 17 mm	K 400	Ø 3 x 40 mm	10000 1/min	10 pieces
	M-25110	Ø 30 x 17 mm	K 400	Ø 3 x 40 mm	8000 1/min	10 pieces

Grit Fleece

Very Coarse = K 60, Coarse = K 80, Medium = K 180, Fine = K 240, Very Fine = K 400, Ultra Fine = K 1000