

Pipe brushes

Nylon with silicon carbide

Pipe brushes

Pipe brushes are ideally suited for deburring and cleaning work in crossways drillings and insertions.

The flexible trimming made of nylon prevents breakage of the material even with the highest stress and deformation.

The pipe brushes are available in two different versions:

- nylon standard with silicon carbide
- nylon standard with corundum

Nylon Silicon Carbide Pipe Brushes - SiC



Part No.	Abrasive	Head dimensions	Grit size	Shank dimensions	Total length	Rotation speed max.	
M-15000	SiC	Ø 0.7 x 12 mm	K 1000	Ø 0.42 mm	100 mm	700 1/min	1
M-15002	SiC	Ø 1.2 x 12 mm	K 1000	Ø 0.47 mm	100 mm	700 1/min	1
M-15004	SiC	Ø 1.9 x 18 mm	K 1000	Ø 0.74 mm	100 mm	700 1/min	1
M-15006	SiC	Ø 2.2 x 18 mm	K 1000	Ø 0.94 mm	100 mm	700 1/min	1
M-15008	SiC	Ø 2.6 x 25 mm	K 1000	Ø 1.08 mm	100 mm	700 1/min	1
M-15010	SiC	Ø 3.2 x 25 mm	K 1000	Ø 1.66 mm	100 mm	700 1/min	1
M-15012	SiC	Ø 3.5 x 25 mm	K 1000	Ø 1.66 mm	100 mm	700 1/min	1

Using nylon pipe brushes smooths the surface and positively influences the latter for subsequent use. The twisted wire is zinc-coated. Linear use by hand and clockwise in machines.

Nylon-Corundum Pipe Brushes - Corundum



Part No.	Abrasive	Head dimensions	Grit size	Shank dimensions	Total length	Rotation speed max.	
M-15014	Corundum	Ø 4.2 x 25 mm	K 600	Ø 2.2 mm	125 mm	700 1/min	1
M-15016	Corundum	Ø 4.8 x 25 mm	K 600	Ø 2.2 mm	125 mm	700 1/min	1
M-15018	Corundum	Ø 5.5 x 25 mm	K 600	Ø 2.2 mm	125 mm	700 1/min	1
M-15020	Corundum	Ø 6.6 x 25 mm	K 600	Ø 3 mm	125 mm	700 1/min	1
M-15022	Corundum	Ø 8.2 x 25 mm	K 600	Ø 3 mm	125 mm	700 1/min	1
M-15024	Corundum	Ø 9.8 x 25 mm	K 600	Ø 3.4 mm	125 mm	700 1/min	1
M-15026	Corundum	Ø 11.5 x 25 mm	K 600	Ø 3.4 mm	125 mm	700 1/min	1
M-15028	Corundum	Ø 13.0 x 25 mm	K 600	Ø 4.2 mm	125 mm	700 1/min	1
M-15030	Corundum	Ø 16.0 x 25 mm	K 600	Ø 4.2 mm	125 mm	700 1/min	1
M-15032	Corundum	Ø 17.5 x 25 mm	K 600	Ø 4.2 mm	125 mm	700 1/min	1
M-15034	Corundum	Ø 19.4 x 25 mm	K 600	Ø 5.6 mm	125 mm	700 1/min	1
M-15036	Corundum	Ø 22.6 x 25 mm	K 600	Ø 5.6 mm	125 mm	700 1/min	1
M-15038	Corundum	Ø 25.8 x 25 mm	K 600	Ø 6.2 mm	125 mm	700 1/min	1

Using nylon pipe brushes smooths the surface and positively influences the latter for subsequent use. The twisted wire is zinc-coated. Linear use by hand and clockwise in machines.