


EJECTOR PINS

Ejector Pins, DIN 6751, Type AB - Nitrided



d1 g6	d2 -0,2	k -0,05	R	d3	100	125	160	200	250	L 0/+2	315	400	500	630	800	1000
1,5	3	1,5	0,2	$d_1 + 0,03$	•	•	•	•	•	315						
2,0	4	2			•	•	•	•	•	400						
2,2			0,3		•	•	•	•	•	500						
2,5	5	3			•	•	•	•	•	630						
3,0	6				•	•	•	•	•	800						
3,2					•	•	•	•	•	1000						
3,5	7				•	•	•	•	•							
3,7					•	•	•	•	•							
4,0	8				•	•	•	•	•							
4,2					•	•	•	•	•							
4,5					•	•	•	•	•							
5,0	10				•	•	•	•	•							
5,2					•	•	•	•	•							
6,0	12	5	0,5		•	•	•	•	•							
6,2					•	•	•	•	•							
8,0	14				•	•	•	•	•							
8,2				$d_1 + 0,04$	•	•	•	•	•							
10,0	16				•	•	•	•	•							
10,2					•	•	•	•	•							
11,0					•	•	•	•	•							
12,0	20	7	0,8		•	•	•	•	•							
12,2					•	•	•	•	•							
12,5					•	•	•	•	•							
14,0	22				•	•	•	•	•							
16,0					•	•	•	•	•							
20,0	26	8	1	$d_1 + 0,1$	•	•	•	•	•							
25,0	32	10				•	•	•	•							
32,0	40					•	•	•	•							

Surface: Nitrided and Polished.

Material: 1.2344.

Hardness: 65 ± 2 HRC. Head 45 ± 5 HRC.

Order example

UDSAB+d1+L ex. UDSAB4160 (4x160 mm).