





PARALLEL GRIPPER



INORMA	A	B	C	D	E	F	G	OPEN	CLOSE	FORCE(IN)OPEN/CLOSE	WEIGHT(g)
NPC.MHZ210S	23	57	29	16	23	16.4	M3	15.2	11.2	/14.2	55
NPC.MHZ210D	23	57	29	16	23	16.4	M3	15.2	11.2	22/34	55
NPC.MHZL210D	23	57	35	16	25	16.4	M3	19.2	11.2	22/34	59
NPC.MHZ216S	30.6	67.3	38	24	24.5	23.6	M5	20.9	14.9	/54	123
NPC.MHZ216D	30.6	67.3	38	24	24.5	23.6	M5	20.9	14.9	68/90	120
NPC.MHZL216D	30.6	70	47	24	31	23.6	M5	26.9	14.9	68/90	130
NPC.MHZ220S	42	84.8	50	30	29	27.6	M5	26.3	16.3	/66	227
NPC.MHZ220D	42	84.8	50	30	29	27.6	M5	26.3	16.3	84/132	225
NPC.MHZL220D	42	90	62	30	36	27.6	M5	34.3	16.3	84/132	211
NPC.MHZ225S	52	102.7	63	36	30	33.6	M5	33.3	19.3	/90	309
NPC.MHZ225D	52	102.7	63	36	30	33.6	M5	33.3	19.3	130/208	314
NPC.MHZL225D	52	106	75	36	40	33.6	M6	41.3	19.3	130/208	293
NPC.MHZ232S	60	122	97	46	49	40	M6	48	26	/260	415
NPC.MHZ232D	60	113	97	46	40	40	M6	48	26	316/386	410
NPC.MHZ240S	72	152	119	56	62	48	M8	60	30	/434	543
NPC.MHZ240D	72	139	119	56	49	48	M8	60	30	508/636	537

Air 2-7 bar, temperature 5°C - 60°. Repetibility +- 0,02mm.