



MSM-R - Push in Male Threaded Stud


Part No.	Ø A	G1		Weight (g)
MSM04R1/8	4	R1/8	10	7,5
MSM06R1/8	6	R1/8	10	8
MSM06R1/4	6	R1/4	10	15
MSM08R1/4	8	R1/4	10	14


Material: Technopolymer / Brass (Nickel Plated).

Pressure: Max 10 bar.


Temperature: 0°C to +60°C.

MSW-R - Push in Male Threaded Elbow


Part No.	Ø A	G1		Weight (g)
MSW04R1/8	4	R1/8	10	10
MSW06R1/8	6	R1/8	10	11
MSW06R1/4	6	R1/4	10	19
MSW08R1/4	8	R1/4	10	20

MSTY-R - Push in Male Threaded Y


Part No.	Ø A	G1		Weight (g)
MSTY04G1/8	4	R1/8	10	13
MSTY06G1/8	6	R1/8	10	15
MSTY06G1/4	6	R1/4	10	22

MSA-R - Push in Male Threaded Branch T


Part No.	Ø A	G1		Weight (g)
MSA04R1/8	4	R1/8	10	13
MSA06R1/8	6	R1/8	10	14
MSA06R1/4	6	R1/4	10	22
MSA08R1/4	8	R1/4	10	25